

GAS FURNACES 96%+ AFUE

GE Appliances is proud to offer a full line of residential HVAC equipment that's **PRO**centric, from sale to service. Our range of gas furnaces features a full line of 90% AFUE units with options for single, two-stage, or modulating gas valves and fixed or variable-speed ECM and CT motors. And thanks to features that benefit pros and homeowners, it's never been easier to close the sale.



EASIER TO: DO THE JOB

Insta-Position Technology

When a tight crawl space or attic call for a horizontal furnace, eliminate the hassle of shifting components and save time during install with furnaces that ship ready for install in multiple positions with no internal conversions.

Better Fit

At 33 inches tall, GE Appliances furnaces fit into more spaces and more homes, while taking up less space wherever they're installed — because one inch can make the difference between a successful install and a headache.

Pre-formed Flanges

Our coils are designed for a frustration-free installation with flanges designed to fit matching evaporator coils perfectly, reducing time and the possibility of damage.

Open Backed Wire Connectors

With our open-backed electrical connections, you can take readings without removing a wire, saving you time when testing components.

EASIER TO: CLOSE THE SALE

Quiet Operation

From smaller, more efficient burners, to a startup without clicks and whooshes, to an insulated heat exchanger compartment, these units are designed to keep it quiet.

100,000 Cycle Tested Heat Exchanger

When you tell a customer they can rely on the durability of GE Appliances, you don't have to cross your fingers; we build it and test it so you can stand behind it.

Lower Energy Bills

Homeowners save money on their energy bills with high efficiency, Energy Star Certified furnaces.

Ultra-Low-NOx

GE Appliances Ultra-Low-NOx units produce lower nitrogen oxide emissions, helping mitigate potential health problems and caring for our planet.

Ten-Year Warranty

Your homeowners can double the standard five-year warranty simply by registering their unit and have a lifetime warranty on the heat exchanger. Translation: peace of mind for homeowners.

GAS FURNACES 96%+ AFUE

SPECIFICATIONS



NF97****M

- Modulating gas valve (67 stages)
- Variable speed motor

97% Modulating Gas Furnace

Model	Heat Input BTUs	Capacity (Tons)	Configuration	Dimensions* (H" x W" x D")	Weight (Lbs)
NF97U070M3B	70K	3	Upflow/Horizontal	33 x 17.5 x 28.5	123.5
NF97U090M3C	90K	3	Upflow/Horizontal	33 x 21 x 28.5	146.3
NF97U090M4C	90K	4	Upflow/Horizontal	33 x 21 x 28.5	146.3
NF97U090M5C	90K	5	Upflow/Horizontal	33 x 21 x 28.5	148.2
NF97U110M5C	110K	5	Upflow/Horizontal	33 x 21 x 28.5	166.3
NF97U135M5D	135K	5	Upflow/Horizontal	33 x 24.5 x 28.5	176.7
NF97D070M3B	70K	3	Downflow	33 x 17.5 x 28.5	142.5
NF97D090M4C	90K	4	Downflow	33 x 21 x 28.5	157.7
NF97D110M5C	110K	5	Downflow	33 x 21 x 28.5	165.3



NF97****V

- 2-stage gas valve
- Variable speed ECM

97% 2-Stage Ultra-Low NOx Gas Furnace

Model	Heat Input BTUs	Capacity (Tons)	Configuration	Dimensions* (H" x W" x D")	Weight (Lbs)
NF97X040V3B	40K	3	Upflow/Horizontal	33 x 17.5 x 28.5	118.8
NF97X060V3B	60K	3	Upflow/Horizontal	33 x 17.5 x 28.5	123.5
NF97X080V4C	80K	4	Upflow/Horizontal	33 x 21 x 28.5	146.3
NF97X080V5C	80K	5	Upflow/Horizontal	33 x 21 x 28.5	148.2



NF96****V

- 2-stage gas valve
- Variable speed ECM

96% 2-Stage Gas Furnace

Model	Heat Input BTUs	Capacity (Tons)	Configuration	Dimensions* (H" x W" x D")	Weight (Lbs)
NF96U045V3B	45K	3	Upflow/Horizontal	33 x 17.5 x 28.5	142.5
NF96U070V3B	70K	3	Upflow/Horizontal	33 x 17.5 x 28.5	142.5
NF96U090V3C	90K	3	Upflow/Horizontal	33 x 21 x 28.5	145.4
NF96U090V5C	90K	5	Upflow/Horizontal	33 x 21 x 28.5	156.8
NF96U110V5C	110K	5	Upflow/Horizontal	33 x 21 x 28.5	166.3
NF96U135V5D	135K	5	Upflow/Horizontal	33 x 24.5 x 28.5	176.7
NF96D070V4B	70K	4	Downflow	33 x 17.5 x 28.5	142.5
NF96D090V5C	90K	5	Downflow	33 x 21 x 28.5	157.7
NF96D110V5C	110K	5	Downflow	33 x 21 x 28.5	165.3



NF96****S

- Single-stage gas valve
- Constant torque motor

96% Single-Stage Gas Furnace

Model	BTUs	Capacity (Tons)	Configuration	Dimensions* (H" x W" x D")	Weight (Lbs)
NF96U045S3B	45K	3	Upflow/Horizontal	33 x 17.5 x 28.5	113.1
NF96U070S3B	70K	3	Upflow/Horizontal	33 x 17.5 x 28.5	120.7
NF96U090S4C	90K	4	Upflow/Horizontal	33 x 21 x 28.5	140.6
NF96U110S5C	110K	5	Upflow/Horizontal	33 x 21 x 28.5	151.1
NF96D045S3B	45K	3	Downflow	33 x 17.5 x 28.5	113.1
NF96D070S4B	70K	4	Downflow	33 x 17.5 x 28.5	127.3
NF96D090S4C	90K	4	Downflow	33 x 21 x 28.5	142.5

* Unit height excludes flange